

PGDQ2.MH15654 - Marking and Labeling Systems - Component

Marking and Labeling Systems - Component

MELROSE NAMEPLATE & LABEL CO

26575 Corporate Ave
Hayward, CA 94545-3920 United States

MH15654

Model No.	Application Surface	Min Temp (°C)	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Pressure-sensitive printed labels Description - subsurface printed clear polycarbonate facestock with adhesive which is protected by a release liner						
MLP-009a1						
	Acrylonitrile butadiene styrene	-40	80	X	X	-
	Alkyd paint	-40	80	X	X	-
	Aluminum	-40	80	X	X	-
	Epoxy	-40	80	X	X	-
	Galvanized steel	-40	80	X	X	-
	Nylon - Polyamide	-40	80	X	X	-
	Polyester paint	-40	80	X	X	-
	Polyphenylene oxide/ether	-40	80	X	X	-
	Polycarbonate	-40	60	X	X	-
	Polyurethane paint	-40	60	X	X	-
	Porcelain	-40	60	X	X	-
	Stainless steel	-40	60	X	X	-
	Polyethylene terephthalate	-40	40	X	X	-
MLP-009a2						
	Acrylic powder paint	-40	80	X	-	-
	Alkyd paint	-40	80	X	X	-
	Aluminum	-40	80	X	X	-
	Epoxy	-40	80	X	X	-

	Epoxy powder paint	-40	80	X	X	-
	Epoxy powder paint (textured)	-40	80	X	-	-
	Galvanized steel	-40	80	X	X	-
	Nylon - Polyamide	-40	80	X	X	-
	Polyester powder paint	-40	80	X	-	-
	Polyester powder paint (textured)	-40	80	X	-	-
	Polyphenylene oxide/ether	-40	80	X	X	-
	Polypropylene	-40	80	X	-	-
	Porcelain	-40	80	X	-	-
	Stainless steel	-40	80	X	-	-
	Urethane powder paint	-40	80	X	-	-
	Acrylonitrile butadiene styrene	-40	60	X	X	-
	High density polyethylene	-40	60	X	-	-
	Polycarbonate	-40	60	X	-	-
	Low density polyethylene	-40	40	X	-	-
	Polystyrene	-40	40	X	-	-

Pressure-sensitive printed labels**MLP-010a**

	Acrylic paint	-40	125	X	X	-
	Alkyd paint	-40	125	X	X	-
	Aluminum	-40	125	X	X	-
	Brass	-40	125	X	X	-
	Epoxy paint	-40	125	X	X	-
	Epoxy powder paint	-40	125	X	-	-
	Epoxy/Urethane powder paint	-40	125	X	X	-
	Galvannealed steel	-40	125	X	X	-
	Glass	-40	125	X	X	-
	Polyester paint	-40	125	X	X	-
	Polyester powder paint	-40	125	X	X	-
	Porcelain	-40	125	X	X	-

	Stainless steel	-40	125	X	X	-
--	-----------------	-----	-----	---	---	---

	Melamine	-40	100	X	X	-
	Nylon - Polyamide	-40	100	X	X	-
	Phenolic - Phenol Formaldehyde	-40	100	X	X	-
	Acrylonitrile butadiene styrene	-40	80	X	X	-
	Polybutylene terephthalate	-40	80	X	X	-
	Polycarbonate	-40	80	X	X	-
	Polyethylene	-40	80	X	X	-
	Polyphenylene oxide/ether	-40	80	X	X	-
	Polypropylene	-	80	X	-	-
	Polystyrene	-40	80	X	X	-
	Polyvinyl chloride	-40	80	X	X	-
	Unsaturated polyester - thermoset	-40	80	X	X	-
MLP-010b						
	Acrylic paint	-40	125	X	X	-
	Alkyd paint	-40	125	X	X	-
	Aluminum	-40	125	X	X	-
	Brass	-40	125	X	X	-
	Epoxy paint	-40	125	X	X	-
	Epoxy powder paint	-40	125	X	-	-
	Epoxy/Urethane powder paint	-40	125	X	X	-
	Galvanized steel	-40	125	X	X	-
	Glass	-40	125	X	X	-
	Polybutylene terephthalate	-40	125	X	X	-
	Polyester paint	-40	125	X	X	-
	Polyester powder paint	-40	125	X	X	-
	Polyethylene terephthalate	-40	125	X	X	-
	Porcelain	-40	125	X	X	-
	Stainless steel	-40	125	X	X	-
	Melamine	-40	100	X	X	-
	Nylon - Polyamide	-40	100	X	X	-
	Phenolic - Phenol Formaldehyde	-40	100	X	X	-

	Polycarbonate	-40	100	X	X	-
	Polyphenylene oxide/ether	-40	100	X	X	-
	Unsaturated polyester - thermoset	-40	100	X	X	-
	Acrylonitrile butadiene styrene	-40	80	X	X	-
	Polyethylene	-40	80	X	X	-
	Polypropylene	-	80	X	-	-
	Polystyrene	-40	80	X	X	-
	Polyvinyl chloride	-40	80	X	X	-
MLP-010c						
	Acrylic paint	-40	125	X	X	-
	Alkyd paint	-40	125	X	X	-
	Aluminum	-40	125	X	X	-
	Brass	-40	125	X	X	-
	Epoxy paint	-40	125	X	X	-
	Epoxy powder paint	-40	125	X	-	-
	Epoxy/Urethane powder paint	-40	125	X	X	-
	Galvanized steel	-40	125	X	X	-
	Glass	-40	125	X	X	-
	Polyester paint	-40	125	X	X	-
	Polyester powder paint	-40	125	X	X	-
	Porcelain	-40	125	X	X	-
	Stainless steel	-40	125	X	X	-
	Phenolic - Phenol Formaldehyde	-40	100	X	X	-
	Polycarbonate	-40	100	X	X	-
	Acrylonitrile butadiene styrene	-40	80	X	X	-
	Melamine	-40	80	X	X	-
	Nylon - Polyamide	-40	80	X	X	-
	Polybutylene terephthalate	-40	80	X	X	-
	Polyethylene	-40	80	X	X	-
	Polyphenylene oxide/ether	-40	80	X	X	-
	Polypropylene	-40	80	X	-	-

	Polystyrene	-40	80	X	X	-
	Polyvinyl chloride	-40	80	X	X	-
	Unsaturated polyester - thermoset	-40	80	X	X	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

Note - (1) The following alternate nomenclature may be used: "BBS" or "BB Stainless", "C" or "Clear", "CM" or "Clear Matte", "G" or "Gold", "RBBS" or "RBB Stainless", "S" or "Silver", "SM" or "Silver Matte", "THRMFLM" or "THERMLfilm", "TMP" or "TMPRK" or "TAMPERmark", "W" or "White". (2) Additional characters may be added to the end of the label designation indicating the type of release liner used unless a specific release liner is indicated. (3) Model designations may or may not include hyphens, apostrophes, single quotes, or dashes as part of the nomenclature.

Marking: Company name or tradename "MH15654" and model designation.

Last Updated on 2022-11-17



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."